

Camera Station PT 9W



Specifications

Item Group	1.2
Heating element	Internal automatic thermostat controlled
Video Output	Composite video signal: 1.0V(p-p), 75 Ohms, unbalanced
Power Supply	30VAC 50/60Hz
Power Consumption (Max)	Less than 4A
Operating Condition	
Operating temperature range	-30°C ~ +55°C (heating element inside housing)
Relative humidity to air	100% (Deck watertight equipment)
Salt Mist Test (Test Criteria acc. to DNV Req)	5 % NaCl, 2 Hours continuous spray
Vibration (Test Criteria acc. to DNV Req.)/ (Test res.)	5-100 Hz, +/- 1 mm or 0,7 g / (6,3 g @ $\omega/p \approx 1$)
Ingress Protection	IP 66 (\approx NEMA 4X)
Weight	15 Kg
Material & finish	Stainless steel AISI 316L, Electro polished
Sunshield	Included
Rotating angle & speed, Pan	0-350°, speed: 0°/sec. to 40°/sec
Rotating angle & speed, Tilt	0-180°, speed: 0°/sec. to 20°/sec
Approval	
Type Approval Certificate	Ref. DNV. Certificate no. A-10678
(Temp. humidity, vibration, EMC, Ingress Protection)	(Presented at www.HERNIS.com)
Liquid Tank Capacity	2 Litre
HERNIS Part Number	095437-xxx/xxx

Note: All data in the data sheet are subject to change without any notice.

