

Camera Station, Mini S-7



SPECIFICATIONS

Item Group	1.2
Video Output	Composite video signal: 1.0V(p-p), 75 Ohms, unbalanced, NTSC/ PAL
Resolution	480 (H) TV lines
Signal to Noise ratio	More than 48 dB (AGC OFF)
Sensitivity	3 lux
Power Supply	24VAC 50/60Hz
Power Consumption (Max)	3W
Operating temperature range	-10°C ~ +60°C
Operation humidity	Less than 95% Rh (non-condensing)
Material & finish	Stainless steel AISI 316, Electro polished
Protection	IP 66/67
Dimension Length x Diameter	110 x 111 mm
Weight	2 Kg
HERNIS Part Number	095432-xxx/xx

Note: All data in datasheet are subject to change without any notice.



Part Number	Description
095432-112/10	Cam. Station Mini S7. 1/4" PAL H.R 2,9mm fixed lens
095432-112/11	Cam. Station Mini S7. 1/4" PAL H.R 2,6mm CS-mount lens
095432-112/20	Cam. Station Mini S7. 1/4" PAL H.R 3,8mm fixed lens
095432-112/21	Cam. Station Mini S7. 1/4" PAL H.R 4mm CS-mount lens
095432-112/30	Cam. Station Mini S7. 1/4" PAL H.R 6mm fixed lens
095432-112/31	Cam. Station Mini S7. 1/4" PAL H.R 8mm CS-mount lens
095432-122/10	Cam. Station Mini S7. 1/4" NTSC H.R 2,9mm fixed lens
095732-122/11	Cam. Station Mini S7. 1/4" NTSC H.R 2,6mm CS-mount lens
095432-122/20	Cam. Station Mini S7. 1/4" NTSC H.R 3,8mm fixed lens
095432-122/21	Cam. Station Mini S7. 1/4" NTSC H.R 4mm CS-mount lens
095432-122/30	Cam. Station Mini S7. 1/4" NTSC H.R 6mm fixed lens
095432-122/31	Cam. Station Mini S7. 1/4" NTSC H.R 8mm CS-mount lens